

RADON MONITOR

Model # PTG-9-RN Portable

FEATURES:

- 0.05 pCi/liter (2 Bq/m³) in 1 hour
- 2pCi/liter(74 Bq/m³) in 1 min
- 30 pCi/liter(1000 Bq/m³) in 5 sec
- USER SETTABLE UNITS - PicoCi/ml or Bq/m³ etc.
- WIDE RANGE - DIGITAL ACCURACY
- PROGRAMMABLE DIGITAL READOUT
- SENSITIVE FOR OCCUPATIONAL EXPOSURE
- DYNAMIC BACKGROUND COMPENSATION
- CAN ACTUATE OPTIONAL DIGITAL PRINTER
- BATTERY OPERATION OR AC OPERATION
- BUILT-IN HIGH LEVEL ALARM
- BUILT-IN LOW FLOW ALARM
- BUILT-IN RS-232 COMPUTER INTERFACE
- USE WITH PORTABLE PC AS 1 YEAR DATA BUFFER



Portable PTG-9-RN

DESCRIPTION: Technical Associates PTG-9-RN Radon Monitor is a sensitive, rugged, portable instrument for detection and measurement of airborne radon. Its' subtractive balanced chamber electro - meter circuit decreases background effects to negligible levels and its deionized and filtered intake reduces to negligible levels spurious effects from smoke, dust and existing ionization in the air. Inlet and outlet hoses allow monitoring interiors of fume hoods, exhaust stacks, etc. The PTG-9-RN will measure airborne radon as free Radon gas (with or without Radon Daughters at users option) as low as 1 pCi/l.

All instruments are calibrated at the factory. Calibration check may be performed in the field with a 10 microCurie level beta-gamma source. Chambers may be switched to calibration mode to check linearity of response on a gamma calibration range. User friendly calibration controls are provided.

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE: (818)-883-7043 FAX: (818) 883-6103
e-mail: tagold@nwc.net www.tech-associates.com

RADON MONITOR

Model # PTG-9-RN Portable

SPECIFICATIONS:

- Ranges:** Large, easy to read digital LED readout. Two ranges cover six decades: 2.0 to 2×10^6 picoCurie/liter
- Background:** Essentially eliminated by subtractive balanced chambers.
- Smoke, Dust and Ion Elimination:** Filter and deionizer reduce effects to negligible level.
- Circuit:** Electrometer circuit amplifies net difference between a one liter radon internal chamber and a sealed background chamber of similar configuration.
- Alarms:** Low Air Flow Alarm High Level Alarm: Red Lamp and Audio Alarm.
- Controls:** Front Panel Off-On range switch calibrate switch. Alarm set button.
- Calibration:** Can calibrate internally with radon gas, or on a calibration course, or (at a single point) with optional beta source.
- Printer:** Plug is furnished for optional external serial printer.
- Computer Port:** RS-232 serial port is built in (fully addressable).
- Portability:** PTG-9-RN is provided with carrying handle and optionally with loops for shoulder sling.
- Case:** Deep drawn aluminum case, with handle and gasketed lid, easily clean-able anodized finish.
- Dimensions**

Instrument Case (Including handle): 7"W x 11"L x 7" Tall.

Front Panel: 11" Long x 7" Wide.

- Battery:** 9V rechargeable sealed. **Battery Life:** 20 hours between changes. Battery charger is built-in.
- Weight:** 12 lbs. Shipping weight 15 lbs.

ACCESSORIES and OPTIONS:

- RAL-3A:** Remote Alarm (audible & visual) Model #RAL-3A (including 25 ft. of cable). Can be used to 500 ft.
- iServe-7:** Built-in internet / Ethernet server.
- HTR-7:** Heated Ion Chambers
- WIN-W:** Win-Wedge data logging software.
- MPM-40DT:** Serial Printer with date and time stamp.

TA TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CA 91303
TELEPHONE: (818)-883-7043 FAX: (818) 883-6103
e-mail: tagold@nwc.net www.tech-as-associates.com